

▶ Digital, RSLAB-7 D



- 1| LCD display for speed and time adjustment. Speed, timer and operating mode can be viewed simultaneously.
- 2| Electronic adjustment of speed and timer.
- 3| Plate with 3 bars included.
- 4| PC control via RS232 interface.
- 5| External rotor brushless motor, long life and no electromagnetic interference.
- 6| Over speed detection and protection.
- 7| Protection class according DIN EN60529: IP21

Code	LJN003	LJQ002
Display	LCD	
Speed range	100-800 rpm	100-350 rpm
Type of movement	Orbital	Linear
Diameter orbital de agitación	4 mm	
Operation type	Continuous or scheduled	
Max. weight of shaking	2,5 Kg	
Timer	1 - 1199 min	
Aprox. dimensions	340 x 300 x 100 mm	
Aprox. weight	8,1 Kg	

▶ Digital, RSLAB-7 PRO



- 1| LCD display for speed and time adjustment. Speed, timer and operating mode can be viewed simultaneously.
- 2| Electronic adjustment of speed and timer.
- 3| External rotor brushless motor, long life and no electromagnetic interference.
- 4| Plate with 4 bars included.
- 5| PC control via RS232 interface.
- 6| External rotor brushless motor, long life and no electromagnetic interference.
- 7| Over speed detection and protection.

Code	LJN004	LJQ003
Display	LCD	
Speed range	100-500 rpm	100-350 rpm
Type of movement	Orbital	Linear
Diameter orbital de agitación	10 mm	-
Max. weight of shaking	7,5 Kg	
Operation type	Continuous or scheduled	
Timer	1 - 1199 min	
Aprox. dimensions	420x370x100 mm	
Aprox. weight	13,5 Kg	