



► Magnetic stirrers RSLAB-4C



- 1| Includes Pt1000 temperature probe for temperature stability of +/- 0.2°C (support kit not included).
- 2| Microprocessor technology guarantees temperature and speed accuracy. Heating is stopped if the safety temperature is exceeded.
- 3| LCD display allows display of speed and temperature.
- 4| PC control via RS232 interface with special StirPc software (on request).
- 5| Protection class according to DIN EN60529: IP21.

Code	LBD004
Speed range	100-1500 rpm
Max. volume	20 L
Temperature range	Ambiente - 550°C
Security temperature	580°C
Plate material	Glass ceramic
Plate dimensions	184x184 mm
Approx. dimensions	360 x 215 x 112 mm
Approx. weight	5,3 Kg

► Accessories (not included)



LBM002 Temperature probe  
PT1000



LBM012 Poly-block blue stand  
with 4 holes for 30 mL tubes



LBM005 Temperature probe  
PT1000 with glass coating



LBM013 Poly-block black stand  
with 4 holes for 40 mL tubes



LBM003 Support kit for probe PT1000  
LBM004 Support kit for probe PT1000



LBM014 Poly-block green stand  
with 6 holes for 80 mL tubes



LBM010 Poly-block red stand with  
11 holes for 4 mL tubes



LBM015 Poly block yellow stand with 4  
holes with 16 mL tubes



LBM011 Poly-block purple stand  
with 4 holes for 20 mL tubes